

SRP-2401 CI+



- CI+ certified by Digital TV Labs
- CI/CI+ supported 2 common interface slots
- Playing video files of DivX, MPG, MP4, VOB, MKV and FLV
- Hard Disk Drive capacity could be chosen (500GB or 1 TB)
- HD+ card bundle (optional)

* The "CI Plus" logo is a trademark of CI Plus LLP

HD PVR Satellite Receiver

- Fully DVB-S2 compliant
- 2 common interface slots for Conax, Irdeto, Nagravision, Viaccess, etc.
- SCPC and MCPC receivable from C/Ku-band satellites
- Capable of setting the frequency for SMATV system
- Service switching time less than 1 second
- Enables you to edit services list
- Enables you to edit favorite services list
- 32-bit Color On-Screen Display (OSD)
- Full Picture in Graphic (PIG) function
- Presents Electronic Programme Guide which allows you to navigate through all available services
- 10,000 services TV (7,000) & Radio (3,000) programmable
- Displays a variety of subtitle
- Subtitle supported
- Enables you to protect your children from adult services
- Firmware update by network and USB-stick
- Able to downmix Dolby to stereo
- Plays back recorded programmes at up to 64 times speed
- Playback of the selected region repeatedly
- Capable of time-shifting
- Powerful trick mode supported
- HDMI connectors and RCA A/V output
- VFD display for service information
- Online game embedded (Battle Tank)

SRP-2401CI+



Tuner & Channel Decoder

Input/ Loop through Connector	F-type, IEC 169-24, Female
Frequency Range	950 ~ 2150MHz
LNB Power & Polarization	Vertical : +13.5VDC Horizontal : +18.5VDC Current : Max. 500mA with Overload Protection
22KHz Tone	Frequency : 22±1KHz Amplitude : 0.65±0.2V
2 Tuners	DVB-S2
Demodulation	QPSK, 8PSK
Input Symbol Rate	1~45MSPS(DVB-S QPSK),
Code Rate	10~30MSPS(DVB-S2 QPSK/8PSK) QPSK:1/2,3/5,2/3,3/4,4/5,5/6,8/9,9/10 8PSK:3/5,2/3,3/4,5/6,8/9,9/10"

DVB Compliant A/V Decoding

Aspect Ratio	4:3, 16:9
Video Resolution	576i, 576p, 720p, 1080i

Conditional Access Interface

PCMCIA	2 slots
	DVB Common Interface standard

A/V & Data In/Out

RCA A/V	HD Video YPbPr, SD Video CVBS output, Audio L/R output
HDMI	HD Digital Video/Audio output
Optical, Coaxial S/PDIF	Digital audio or Dolby AC3 bitstream output, DTS output
TV-Scart	Video CVBS/S-VIDEO/RGB Output Audio L/R output
VCR-Scart	Video CVBS output Audio L/R output Video CVBS/RGB/YUV input for bypass Audio L/R input for bypass
Ethernet	10/100M Base-T
eSATA	External SATA
USB	USB 2.0 Host type(Front 2 port, Rear 1 port)

Main System

Main Processor	RISC
----------------	------

Front Panel

Keys	7Key(Stand-by, CH+, CH-, VOL+, VOL-, MENU, OK)
VFD	Service info. or Time display
LEDs	Stand-by LED 1
USB	2Port(USB 2.0 HOST)

Power Supply

Input Voltage	90 ~ 250VAC, 50/60Hz
Type	SMPS (EU EUP applied)
Power Consumption	Running: Max. 60W, Passive Standby: under 1W (EU EUP compliant)
Protection	Separate internal fuse. The input shall have lightning protection.

Physical Specification

Size(W x H x D)	380 x 60 x 260 mm
Weight(Net)	3.1Kg

Topfield Co., Ltd.

Topfield bldg. 207 Geumgok-Dong, Bundang-Gu, Seongnam, Korea, 463-869 Tel: +82 31 778 0800 Fax: +82 31 778 0801 Email: info@i-topfield.com

* Specifications, functions or design of this product shall be subject to change for improvement without any further notice

TOPFIELD[®]
LEADER OF MULTIMEDIA HOME